

**REMARKS**


Entry of the amendments to the specification, claims and abstract before examination of the application is respectfully requested. These claims have been amended to remove multiple dependencies.

If there are any questions regarding this Preliminary Amendment or the application in general, a telephone call to the undersigned would be appreciated since this should expedite the prosecution of the application for all concerned.

If necessary to effect a timely response, this paper should be considered as a petition for an Extension of Time sufficient to effect a timely response, and please charge any deficiency in fees or credit any overpayments to Deposit Account No. 05-1323 (Docket # 095309.57889US).

Respectfully submitted,

Date: June 19, 2006

  
Vincent J. Sunderdick  
Registration No. 29,004

CROWELL & MORING LLP  
Intellectual Property Group  
P.O. Box 14300  
Washington, DC 20044-4300  
Telephone No.: (202) 624-2500  
Facsimile No.: (202) 628-8844  
GRE:VJS:smw  
2787234#

10/583388

## Cover arrangement for a motor vehicle

BACKGROUND AND SUMMARY OF THE INVENTION

[0001] The invention relates to a cover arrangement for a motor vehicle, ~~as claimed in the preamble to patent claim 1.~~

[0002] Such a cover arrangement is described in German patent application 103 207 42.2. ~~In that cover arrangement,~~ wherein an elastically mounted disk attached to the pivotably movable cover surmounts the gap between the pivotably movable cover and the adjacent connection construction element. In order that a secure jamming protection for the hand of an operator is provided between the prominent disk and the underlying surface of the connection construction element – for example, during closing of the pivotably movable cover - the disk is elastically mounted on the pivotably movable cover. Accordingly, if, due to an operating error on the part of the operator when closing the pivotably movable cover, his or her hand were to find itself between the disk and the surface of the connection construction element, then precautionary measures are available to ensure that no injuries arise therefrom.

[0003] The present invention tackles the problem of providing an elastic mounting of the disk which is simpler in design.

~~[0004] — This object is achieved in a cover arrangement of the generic type by a realization according to the characterizing features of patent claim 1.~~

~~[0005] — Advantageous and expedient embodiments are the subject of the subclaims.~~

[0006] The invention is based on the ~~general notion~~ concept of supporting the disk, which can be an ornamental disk, by a connecting element configured as a simply constructed spring clamp, this connecting element being easily fastenable to the parts to be connected.

[0007] In order to prevent damage to the spring mechanism should the disk tilt, the possible tilt angle is limited by stop means. The tilt angle is designed such that, in particular, fingers of an operator cannot ~~get~~ become jammed in an injury-provoking manner. The tilt angle can be chosen, in particular, such that, as a result of an elastic tilting up of the disk, a clearance of at least 23 mm remains relative to the assigned undersurface on the adjacent connection construction element.

[0008] The whole of the region which is altogether covered by the disk in two mutually adjoining construction elements, namely the pivotably movable cover, on the one hand, and the adjacent connection construction element, on the other hand, can be configured, in particular, as a recess, over which the disk protrudes only slightly outward.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0009] An illustrative embodiment explained in greater detail below is represented in the drawing, in which:

[0010] Fig fig. 1 shows a diagrammatic rear view of a motor vehicle configured as a van, having the cover arrangement according to the invention,

[0011] Fig fig. 2 shows a perspective view, from below, of an ornamental disk forming the cover arrangement according to fig. 1, with a spring clamp fastened to ~~said~~ the ornamental disk,

[0012] Fig fig. 3 shows the bottom side of the ornamental disk in elevation, without spring clamp,

[0013] Fig fig. 4 shows a perspective view of the spring clamp,

[0014] Fig fig. 5a shows a section through the ornamental disk along the line V-V in fig. 1, in the usage position thereof,

[0015] Fig fig. 5b shows an identical section according to 5a, yet with the ornamental disk deflected out of its usage position.

#### DETAILED DESCRIPTION OF THE DRAWINGS

[0016] In fig. 1 a motor vehicle configured as a van can be seen in diagrammatic rear view, which motor vehicle comprises a cover arrangement having a pivotably movable cover in the form of a first leaf door 1 and a connection construction element in the form of a second leaf door 2. The two leaf doors 1, 2 are respectively configured such that they can be pivoted in opposite directions relative to one another about an approximately vertically running swivel axis SA disposed in the corner region between the rear side and side wall of the vehicle. The two leaf doors 1, 2 lie flushly adjacent to one another with the formation of a gap 3. In the illustrative embodiment shown, the gap 3 runs essentially in straight and vertical extent.

[0017] Viewed together with figs 2 to 5, it can be seen how an ornamental disk 4 is disposed in a recess 5 formed by the two leaf doors 1, 2 and there covers the gap 3.

[0018] In the illustrative embodiment, the two leaf doors 1, 2 are conventionally formed in metal-plate shell construction. The first leaf door 1 ~~here comprises~~ includes a marginal region lying adjacent to the second leaf door 2. Beneath a door handle 6 disposed on the first leaf door 1, the ornamental disk 4 is provided in the aforementioned recess 5. The ornamental disk 4, which can be configured outwardly as a marque, for example as a Mercedes star, is thus

disposed in a central region between the leaf doors 1 and 2. The actually straight course of the gap 3 is hereupon altered by the ornamental disk 4 in the area of its placement.

[0019] The ornamental disk 4 is fastened by a U-shaped spring clamp 7 in a region of the recess 5 which is assigned to the first leaf door 1.

[0020] At least the rear-side region of the ornamental disk 4, which region is facing the recess 5, can consist of plastic and can be produced by the injection molding process.

[0021] The spring clamp 7 is connected to the disk 4 by a snap fastening. For this purpose, as snap-fastening means on the rear side of the disk 4, a yoke 8 is provided, by which one of the two U-arms of the spring clamp 7 is displaceable in a slide fit. As additional snap-fastening means, on the rear side of the disk 4 outside the yoke 8, yet within the path of displacement defined by the latter for the arm of the spring clamp 7, a pin 9 is molded on. On the spring clamp 7, one of the two U-arms serves as snap-fastening means, in whose free end region a cutout 10, complementarily matched to the pin 9, is provided. The snap fastening is closed by that U-arm of the spring clamp 7 which has the cutout 10 being pushed through the yoke 8 until the pin 9 snaps into the cutout 10. To enable a snap-locking to take place, the U-arm of the spring clamp 7 must be slid onto the pin 9 under elastic pretensioning. The U-arm can then snap by means of the cutout 10 on the pin 9, with the relief of its pretensioning. When the U-arm is slid through the yoke 8, in order to pretension this arm to obtain the snap fastening, an inclined bar 11 is molded onto the free end of the U-arm. The bar 11 thus serves as a "lead-in accessory", so that the spring clamp 7, with its arm containing the cutout 10, can be slid over the pin 9 as easily as possible.

[0022] The spring clamp 7 possesses at its closed end a theoretical rotational axis 12. About this rotational axis 12, the ornamental disk 4 can be tilted or pivoted by elastic deformation.

[0023] The overall possible tilt angle about which the ornamental disk 4 can be tilted is limited. This limitation is achieved by stops, namely stops 13 on the ornamental disk 4 and stops 14 which are molded onto that end of the spring clamp 7 which is fixedly connected to the first door leaf 1. The size of the possible tilt angle is designed such that, when the first door leaf 1 is closed with the door leaf 2 already closed, that region of the ornamental disk 4 which protrudes from the first door leaf 1 in the direction of the second door leaf 2 can be tilted up to the extent that, for example, no finger of an operator can get jammed between the ornamental disk 4 and the recess 5. Thus, as an appropriate safety distance s, one of at least 23 mm, for instance, can be achieved through an appropriately chosen tilt angle limitation.